

CP- UNR-4K4084

8 Ch. H.265 4K Network Video Recorder



Main Features

- Up to 8 channel IP camera input
- Up to 8ch@1080P(4ch@H.265+4ch@H.264) realtime live-view
- H.265/H.264/MJPEG dual codec decoding
- Up to 12Mp resolution preview and playback
- Max 256Mbps incoming bandwidth
- Support 4 SATA HDDs up to 24TB, 3 USB(2 USB3.0), 1 eSATA up to 16TB
- 2 HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UNR-4K4084

8 Ch. H.265 4K Network Video Recorder

Feature	Specification
Processor	Dual-core embedded processor
IP Camera Input	8 channel
Operating System	Embedded LINUX
Two-way Talk	1 channel Input, 1 channel Output, RCA
User Interface	GUI
Video Output	2 HDMI, 1 VGA
Compression	H.264 / MJPEG
Video Resolution	3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
Video Recording	Max 192 Mbps
Video Display Split	1/4/8
Motion Detection	MD Zones: 396(22×18).
Video Loss	Supports
Camera Blank	Supports
Alarm Input	16 channel
Alarm Output	6 channel
Hard Disk	4 SATA ports, up to 24TB, 1 eSATA port
Smart Phone	iPhone, iPad, Android, Windows Phone
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Internal SATA burner/ Network
Max User Account	128 users
Interface Ports	2 HDMI, 1 VGA, 3 USB2.0, 1 RS485, 1 RS232, 1 RJ45
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Ethernet	2 RJ-45 port (10/100M/1000M)
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
Power Supply	Single, DC12V/4A
Power Consumption	17W for normal model(without HDD)

CP- UNR-4K4084

8 Ch. H.265 4K Network Video Recorder

Feature

Working Temp

Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 405mm × 76mm

4.35 Kg (without HDD)