


CP-UNP-3020TL10-P

2 MP Full HD IP IR PTZ Camera



Main Features

- 1/2.8" CMOS Image sensor
- Powerful 30x Optical and 16x Digital zoom
- Support Triple-streams encoding
- Max. 25/30fps@1080P and 50/60fps@720P Resolution
- DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus
- Up to 300 Presets, 8 Tour, 5 Pattern, 5 Auto scan
- Max 400°/s pan speed, 360° endless pan rotation
- IR Range of 100 Mtr.
- Built-in 2/1 alarm in/out, IP66, PoE Plus
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNP-3020TL10-P

2 MP Full HD IP IR PTZ Camera



Feature

Image Sensor
 Effective Pixels
 S/N Ratio
 Minimum Illumination
 Focal Length
 White Balance
 Focus Control
 Angle of View
 Close Focus Distance
 Electronic Shutter
 AGC control
 Back Light Compensation
 Optical Zoom
 Digital Zoom
 Pan Travel
 Tilt Travel
 Presets
 Preset Speed
 Privacy Masking
 Special Features
 Power up Action
 Idle Motion
 Time Task
 Day/Night: IR Cut Filter
 Video Compression
 Video Streaming
 Audio Compression
 Audio Streaming
 Protocols

Specification

1/2.8" CMOS
 1944(H) x 1092(V), 2Megapixels
 More than 55dB
 Color: 0.05Lux@F1.6; 0Lux@F1.6(IR on)
 4.5mm ~ 135mm
 Auto, ATW, Indoor, Outdoor, Manual
 Auto / Manual
 H: 67.8° ~ 2.4°
 100mm~ 1000mm
 1/3 ~ 1/30,000s
 Auto / Manual
 BLC / HLC / DWDR
 30x
 16x
 0° ~ 360° endless, Pan Speed: 0.1° ~ 300°/sec
 -15° ~ 90°, auto flip 180°, Tilt Speed: 0.1° ~ 200°/sec
 300
 Pan: 400° /s; Tilt: 300° /s
 Up to 24 areas
 IR Range of 100 Mtr., Up to 300 Presets, 8 Tour, 5 Pattern, 5 Auto scan
 Auto restore to previous PTZ and lens status after power failure
 Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period
 Auto activation of Preset/Pan/Scan/Tour/Pattern by presettime
 Auto(ICR) / Color / B/W
 H.264+/H.264 / MJPEG
 Main Stream: 1080P/ D1 (1 ~ 25/30fps), 720P(1~50/60fps), Sub Stream 1: D1/CIF(1 ~ 25/30fps), Sub Stream 2: 720P/ D1/ CIF (1 ~ 25/30fps)
 G.711a / G.711u(32kbps)/ PCM(128kbps)
 1/1 channel In/Out
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x, ONVIF PSIA CGI



*Product casing and specifications are subject to change without prior notice

CP- UNP-3020TL10-P

2 MP Full HD IP IR PTZ Camera



Feature

Alarm
Max Remote Users
Memory Slot
Smart Phone
Operating Temperature
Weather Proof Standard
Dimension
Weight
Power Source
Power Consumption

Specification

2/1 channel In/Out
20 users
Micro SD, Max 128GB
iPhone, iPad, Android, Windows Phone
-40°C ~ 70°C / Less than 90% RH
IP66
Φ186mm x 309 (mm)
3.5 kg
AC24V/ DC12V, POE plus(802.3at)
DC12V: 13W, 20W (IR on), AC24V: 13W, 23W (IR on)