

DS-2CD6510DT-I 1.3MP Network Mini Dome Camera



DS-2CD6510DT-I is applicable to vehicle scenarios such as the train, the public bus and school bus, as well as those with higher requirements for the vibration, riot and waterproof, key features including:

- Up to 1280×960 @ 30 fps for real-time output
- ROI and SVC are adopted with high compression ratio, flexible disposal and low bitrate
- Code smoothness setting for different requirements of image quality and fluency.
- OSD color optional
- Day/Night parameters independent configuration
- PoE power supply is supportable
- Small and nice
- 3-axis adjustment for convenient installation
- 3D DNR and DWDR
- Support two streams and cellphone surveillance
- Support analog output
- Rotate mode, BLC, auto electronic shutter are for different environment
- Function: Heartbeat, mirror, instant recovery, etc.
- Smart detection: Intrusion detection, line crossing detection
- Support VCA, which is compatible with NVR for the second time of video searching and analyzing
- Support EZVIZ
- Support security certificate as HTTPS, SSH; support creating certificate
- Basic and digest authentication is supportable in IE configuration
- Vandal proof: IK08, IP54
- Professional certifications: EN 50155, EN 50121




DS-2CD6510DT-I

3MP Network Mini Dome Camera

Specification

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Speed	1/50s~1/100,000s
Lens	2.8mm, horizontal view angle 80°(4mm/6mm optional)
Angle of Adjustment	H: -30°~30°, V: 0°~75°, R: 0°~360°
Lens Mount	M12
Day & Night	ICR
DNR	3D Digital Noise Reduction
DWDR	Digital Wide Dynamic Range
Compression Standard	
Video Compression	H.264/MJPEG
H.264 Type	Base Line Profile/Main Profile
Video Bit Rate	32Kbps~8Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)
Image	
Max. Resolution	1280 × 960
Frame Rate	50Hz: 25fps (1280 × 960,1280 × 720) 60Hz: 30fps (1280 × 960,1280 × 720)
Image Setting	Rotate mode, Saturation, Brightness, Contrast, etc. are adjusted via client or web-browser
BLC	Regions can be selected
ROI	Support
Network	
Network Storage	NAS (Support NFS,SMB/CIFS)
Intelligent Alarm	Intrusion detection, Line crossing detection, Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage error
Protocol Supportable	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Interface protocol	ONVIF,PSIA,CGI,ISAPI
General	Flickerless, dual stream, heartbeat, mirror, password protection, video masking, watermark
Interface	
Communication	1-ch M12 10M / 100M self-adaptive Ethernet port
Audio Input / Output	1 audio input / 1 audio output (4 Pin Plug)
General	
Working temperature and humidity	-30 °C – 60 °C Humidity 95% or less (non-condensing)
Power Supply	DC24V, range DC16.8V~DC30V
Power	4W MAX

Dimensions



IR Distance	10m
Ingress Protection	IP54
Impact Protection	IK08
Dimensions (mm)	$\Phi 110 \times 63$
Weight	510g

Order Models:

DS-2CD6510DT-I: M12 Ethernet ports, Molex power connector