

RE-737MC

## Addressable System Single Loop System



### Product Overview

- Inbuilt Isolator.
- Supervised a Class 'B' Style 'Y' output circuit.
- Module Status by RED LED.
- Analogue Communication with the panel.
- Module Addressing by Software / 8 way DIP switches.
- Low Standby Current.
- Available with suitable back boxes.



## Features Specification:

- Inbuilt Isolator.
- Supervised a Class 'B' Style 'Y' output circuit.
- Module Status by RED LED.
- Analogue Communication with the panel.
- Module Addressing by Software / 8 way DIP switches.
- Low Standby Current.
- Available with suitable back boxes.

## Mechanical Specification:

Dimensions	(95 W X 75 H X 24D) mm
Color	Black
Weight	0.35 Kg

## Ordering Information

Model	Description
RE – 737MC	Analogue Addressable Control Module

## Electrical Specification:

Operating Voltage	24 VDC Nominal.
Current Draw	2 mA Max.
Standby Current	0.5 mA
End of Line Resistor	47K Ohms
Line Loss	4 VDC Max
External Supply Voltage	Regulated 24V
Operating Temperature	0 °C to 49 °C / 32° – 120 °F
Relative Humidity	93 ± 2% RH (non-condensing) at 32 ±2° C / 90 ±3° F.

